



AMERICAN BEARING MFG.CORP.



625LLB Bearing 2D drawings and 3D CAD models

5,000 mm x 16,000 mm x 5,000 mm NTN
625LLB deep groove ball bearings

Bearing No. 625LLB

Size	5x16x5 mm
Bore Diameter	5,000 mm
Outer Diameter	16,000 mm
Width	5,000 mm
d	5,000 mm
D	16,000 mm
B	5,000 mm
C	5,000 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	5MM Bore; 16MM Outside



AMERICAN BEARING MFG.CORP.

	Diameter; 5MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage; No
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal Shell Alvania Prelubricated
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Bore	0.197 Inch 5 Millimeter
Outside Diameter	0.63 Inch 16 Millimeter
Outer Race Width	0.197 Inch 5 Millimeter
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	5 mm
precision rating:	ISO Class 0
outside diameter:	16 mm
finish/coating:	Uncoated
overall width:	5 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	5 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	5 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	37000 rpm



AMERICAN BEARING MFG.CORP.

internal clearance:	CN
fillet radius:	0.3 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	44000 RPM
dynamic load capacity:	1760 N
series:	Micro
static load capacity:	680 N
manufacturer product page:	Click here