



## AMERICAN BEARING MFG.CORP.



41,275 mm x 101,6 mm x 36,068 mm NTN  
4T-526/522 tapered roller bearings

Bearing No. 4T-526/522

4T-526/522 Bearing 2D drawings and 3D CAD models

Size	41.275x101.6x36.068 mm
Bore Diameter	41,275 mm
Outer Diameter	101,6 mm
Width	36,068 mm
d	41,275 mm
D	101,6 mm
T	36,068 mm
B	36,068 mm
C	26,988 mm
a	22 mm
rs min	3.5 mm
r1s min	3.3 mm
e	0.29
Y2	2.1
Y0	1.16
Mass	1.42 kg
Dynamic load, C	135 kN
Rating life coefficient, A2	1.4
Static load, C0	165 kN
Nlim (oil)	5,000 rpm
Nlim (grease)	3,800 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
Characteristic cage	0.42 Hz



## AMERICAN BEARING MFG.CORP.

frequency, FTF	
Characteristic rolling element frequency, BSF	5.6 Hz
Characteristic outer ring frequency, BPF0	6.22 Hz
Characteristic inner ring frequency, BRFI	8.78 Hz
ra max	3.5 mm
r1a max	3.3 mm